

SCAN Active Antenna is designed to provide reliable connectivity through your Thuraya IP, thus enhancing the performance of Standard IP and Streaming IP.

The antenna is best suited for customers in the media industry who require a compact, reliable and easy to carry/setup solution for streaming videos while on the field. SCAN Active Antenna connects quickly and conveniently as if you were back in the news room.

#### Key Features:

- Enables 384 kbps streaming IP uplink and downlink
- Compact in size and easy to carry
- Cable length up to 30m
- Easily pointed towards satellite
- Built-in GPS antenna
- Battery powered for portable use
- DC powered for fixed installations



# Physical Characteristics

Weight

Size Colour

Cable

Connector

Bandwidth Capabilities

### Tolerances

### Electrical

## Battery

#### GPS

Operating temperature range  OC to +55C when using DC power  OC to +50C when using batteries  OC to +40C when charging batteries  Survival temperature range  -20C to +60C with battery included  -40C to +85C without battery  Environmental conditions  Ingress protection IP55  Transmission  Receive mode G/T:  Min18dB/K, typ -16dB/K  Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency  1525.0 - 1559.0 MHz  1626.5 - 1660.5 MHz	
0C to +50C when using batteries 0C to +40C when charging batteries  Survival temperature range -20C to +60C with battery included -40C to +85C without battery  Environmental conditions Ingress protection IP55  Transmission Receive mode G/T: Min18dB/K, typ -16dB/K Transmit mode EIRP: Min. 15dBW, typ 16dBW  Frequency 1525.0 - 1559.0 MHz	
0C to +50C when using batteries 0C to +40C when charging batteries  Survival temperature range -20C to +60C with battery included -40C to +85C without battery  Environmental conditions Ingress protection IP55  Transmission Receive mode G/T: Min18dB/K, typ -16dB/K Transmit mode EIRP: Min. 15dBW, typ 16dBW  Frequency 1525.0 - 1559.0 MHz	
OC to +40C when charging batteries  Survival temperature range -20C to +60C with battery included -40C to +85C without battery  Environmental conditions Ingress protection IP55  Transmission Receive mode G/T: Min18dB/K, typ -16dB/K Transmit mode EIRP: Min. 15dBW, typ 16dBW  Frequency 1525.0 - 1559.0 MHz	
Survival temperature range -20C to +60C with battery included -40C to +85C without battery  Environmental conditions Ingress protection IP55  Transmission Receive mode G/T: Min18dB/K, typ -16dB/K Transmit mode EIRP: Min. 15dBW, typ 16dBW Frequency 1525.0 - 1559.0 MHz	
-40C to +85C without battery  Environmental conditions Ingress protection IP55  Transmission Receive mode G/T:  Min18dB/K, typ -16dB/K  Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency 1525.0 - 1559.0 MHz	
Environmental conditions  Ingress protection IP55  Transmission  Receive mode G/T:  Min18dB/K, typ -16dB/K  Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency  1525.0 - 1559.0 MHz	
Transmission Receive mode G/T:  Min18dB/K, typ -16dB/K  Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency 1525.0 - 1559.0 MHz	
Min18dB/K, typ -16dB/K  Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency  1525.0 - 1559.0 MHz	
Min18dB/K, typ -16dB/K Transmit mode EIRP: Min. 15dBW, typ 16dBW Frequency 1525.0 - 1559.0 MHz	
Transmit mode EIRP:  Min. 15dBW, typ 16dBW  Frequency  1525.0 - 1559.0 MHz	
Min. 15dBW, typ 16dBW Frequency 1525.0 - 1559.0 MHz	
Frequency 1525.0 - 1559.0 MHz	
1626.5 - 1660.5 MHz	
Polarisation LHCP	
Axial ratio <2dB	
Power Consumption:	
Min 3W, typ 18W, max 24W	
Supply:	
12 - 24 V DC via coax	
19V charging voltage	
Connector QMA (snap-on) female	
Battery type Rechargeable Li-lon	
Battery life >300 charge cycles	
Transmit time Standard mode >3hrs	
384 kbps streaming >1hr	
RHCP patch antenna	
Frequency 1575.42 MHz	
Gain 25dB	
2300	
NF 1.2dB	

QMA (snap-on) female

1.55kg without battery
1.80kg with battery

30m)

270mm x 155mm x 60mm

Light grey radome with grey aluminium base

Fixed length coaxial cables (6m, 10m, 15m,

SCAN ANTENNA A/S
Dyregaardsvej 1-3
2740 Skovlunde
Denmark
Tel: (+45) 4333 1620
Fax (+45) 4494 1099
Email: info@scan-antenna.com
Website: www.scan-antenna.com

